















特徴番号	タイプ	接続口 (インチ)	全高 (mm)	最大幅 (mm)	接液部材質	装填可能 フィルター	耐圧 (Mpa)	写真	在庫数 (2023年3月8日時点)	詳細	単価 (円)	最小販売ロット (本)
200-001-001	樹脂タイプ	1/4	299	116	PP NBR	全長 250mm 内径 28mm 外径 60~67mm DOEタイプ	0.49		105	不透明タイプ	500	5
200-001-002	樹脂タイプ	3/8	299	116	PP NBR	全長 250mm 内径 28mm 外径 60~67mm DOEタイプ	0.49		73	不透明タイプ	500	5
200-001-003	樹脂タイプ	1/4	178	120	PP NBR	全長 125mm 内径 28mm 外径 60~67mm DOEタイプ	0.49		70	不透明タイプ	400	5

200-001-004	樹脂タイプ	1/4	299	116	PP NBR	全長 250mm 内径 28mm 外径 60~67mm DOEタイプ	0.49	  	16	不透明タイプ	500	5
200-020-006	樹脂タイプ	3/8	320	133	PP NBR SUS304	全長 250mm 内径 28mm 外径 60~67mm DOEタイプ	0.49	  	12	不透明タイプ	600	5
200-020-001	樹脂タイプ	1/2	320	133	PP AS NBR SUS304	全長 250mm 内径 28mm 外径 60~67mm DOEタイプ	0.42	  	32	透明タイプ	800	5

200-020-002	樹脂タイプ	3/4	320	133	PP AS NBR SUS304	全長250mm 内径 28mm 外径 60~67mm DOEタイプ	0.42	  	22	透明タイプ	800	5
200-020-003	樹脂タイプ	3/8	320	133	PP AS NBR SUS304	全長 250mm 内径 28mm 外径 60~67mm DOEタイプ	0.42	  	20	透明タイプ	800	5
200-100-001	樹脂タイプ	3/4	610	185	PP NBR SUS304	全長 508mm 内径 28mm 外径 110~115m DOEタイプ	0.49	  	105	不透明タイプ	2,000	3



200-100-002	樹脂タイプ	1	610	185	PP PC NBR SUS304	全長 508mm 内径 28mm 外径 110~115mm DOEタイプ	0.49		16	透明タイプ	3,000	3
200-500-001	SUSタイプ	2	1,365	390	SUS304 NBR 真鍮	全長 1000mm 内径 28mm 外径 60~65mm DOEタイプ フィルター5本装填	0.5		2	SUSタイプ	35,000	1
200-500-002	SUSタイプ	1・1/2	610	390	SUS304 NBR 真鍮	全長 250mm 内径 28mm 外径 60~65mm DOEタイプ フィルター7本装填	0.5		7	SUSタイプ	30,000	1

200-500-003	SUSタイプ	1・1/2	1,092	370	SUS304 NBR 真鍮	全長 1000mm 内径 28mm 外径 60~65mm DOEタイプ フィルター3本装填	0.5	    	1	SUSタイプ	30,000	1
200-020-004	樹脂タイプ	3/4	310	115	PP FKM	全長 250mm 内径 28mm 外径 60~67mm DOEタイプ	0.49	  	70	不透明タイプ	1,500	2
200-020-005	樹脂タイプ	3/4	570	136	PP FKM	全長 508mm 内径 28mm 外径 60~67mm DOEタイプ	0.49	  	12	不透明タイプ	2,000	2